

BGD902

860 MHz, 18.5 dB gain power doubler amplifier

Rev. 08 — 7 June 2007

Product data sheet

1. Product profile

1.1 General description

Hybrid amplifier module in a SOT115J package operating with a supply voltage of 24 V.

1.2 Features

- Excellent linearity
- Extremely low noise
- Excellent return loss properties
- Silicon nitride passivation
- Rugged construction
- Gold metallization ensures excellent reliability

1.3 Applications

- CATV systems operating in the 40 MHz to 900 MHz frequency range.

1.4 Quick reference data



Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$f = 50$ MHz	18.2	18.5	18.8	dB
		$f = 900$ MHz	19	19.5	20	dB
I_{tot}	total current consumption (DC)	[1]	405	420	435	mA

[1] The module normally operates at $V_B = 24$ V, but is able to withstand supply transients up to 35 V.

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Symbol
1	input		
2, 3	common		
5	+ V_B		
7, 8	common		
9	output		

3. Ordering information

Table 3. Ordering information

Type number	Package		Version
	Name	Description	
BGD902	-	rectangular single-ended package; aluminium flange; 2 vertical mounting holes; 2 × 6-32 UNC and 2 extra horizontal mounting holes; 7 gold-plated in-line leads	SOT115J

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_B	supply voltage		-	30	V
V_i	RF input voltage		-	70	dBmV
T_{stg}	storage temperature		-40	+100	°C
T_{mb}	mounting base temperature		-20	+100	°C

5. Characteristics

Table 5. Characteristics

Bandwidth 40 MHz to 900 MHz; $V_B = 24$ V; $T_{mb} = 35$ °C; $Z_S = Z_L = 75$ Ω.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	f = 50 MHz	18.2	18.5	18.8	dB
		f = 900 MHz	19	19.5	20	dB
SL	slope cable equivalent	f = 40 MHz to 900 MHz	0.4	0.9	1.4	dB
FL	flatness of frequency response	f = 40 MHz to 900 MHz	-	±0.15	±0.3	dB
S_{11}	input return losses	f = 40 MHz to 80 MHz	21	23	-	dB
		f = 80 MHz to 160 MHz	22	24	-	dB
		f = 160 MHz to 320 MHz	21	24	-	dB
		f = 320 MHz to 550 MHz	18	23	-	dB
		f = 550 MHz to 650 MHz	17	23	-	dB
		f = 650 MHz to 750 MHz	16	24	-	dB
		f = 750 MHz to 900 MHz	16	26	-	dB
S_{22}	output return losses	f = 40 MHz to 80 MHz	25	32	-	dB
		f = 80 MHz to 160 MHz	23	31	-	dB
		f = 160 MHz to 320 MHz	20	29	-	dB
		f = 320 MHz to 550 MHz	20	28	-	dB
		f = 550 MHz to 650 MHz	19	31	-	dB
		f = 650 MHz to 750 MHz	18	29	-	dB
		f = 750 MHz to 900 MHz	17	22	-	dB

Table 5. Characteristics ...continued

Bandwidth 40 MHz to 900 MHz; $V_B = 24\text{ V}$; $T_{mb} = 35\text{ °C}$; $Z_S = Z_L = 75\text{ }\Omega$.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit	
S_{21}	phase response	$f = 50\text{ MHz}$	-45	-	+45	deg	
CTB	composite triple beat	49 chs flat; $V_o = 47\text{ dBmV}$; $f_m = 859.25\text{ MHz}$	-	-68.5	-67	dB	
		77 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 547.25\text{ MHz}$	-	-70	-68	dB	
		110 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 745.25\text{ MHz}$	-	-63.5	-62	dB	
		129 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 859.25\text{ MHz}$	-	-60	-58	dB	
		110 chs; $f_m = 400\text{ MHz}$; $V_o = 49\text{ dBmV}$ at 550 MHz	[1]	-	-64	-62	dB
		129 chs; $f_m = 650\text{ MHz}$; $V_o = 49.5\text{ dBmV}$ at 860 MHz	[2]	-	-58.5	-56.5	dB
X_{mod}	cross modulation	49 chs flat; $V_o = 47\text{ dBmV}$; $f_m = 55.25\text{ MHz}$	-	-66.5	-64	dB	
		77 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 55.25\text{ MHz}$	-	-69.5	-67	dB	
		110 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 55.25\text{ MHz}$	-	-66	-63.5	dB	
		129 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 55.25\text{ MHz}$	-	-64.5	-62	dB	
		110 chs; $f_m = 400\text{ MHz}$; $V_o = 49\text{ dBmV}$ at 550 MHz	[1]	-	-63	-60	dB
		129 chs; $f_m = 860\text{ MHz}$; $V_o = 49.5\text{ dBmV}$ at 860 MHz	[2]	-	-61	-58	dB
CSO	composite second order distortion	49 chs flat; $V_o = 47\text{ dBmV}$; $f_m = 860.5\text{ MHz}$	-	-65	-62	dB	
		77 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 548.5\text{ MHz}$	-	-72	-67	dB	
		110 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 746.5\text{ MHz}$	-	-65	-60	dB	
		129 chs flat; $V_o = 44\text{ dBmV}$; $f_m = 860.5\text{ MHz}$	-	-61	-58	dB	
		110 chs; $f_m = 250\text{ MHz}$; $V_o = 49\text{ dBmV}$ at 550 MHz	[1]	-	-67	-63	dB
		129 chs; $f_m = 250\text{ MHz}$; $V_o = 49.5\text{ dBmV}$ at 860 MHz	[2]	-	-62	-58	dB
IMD2	second order distortion		[3]	-	-80	-74	dB
			[4]	-	-83	-77	dB
			[5]	-	-84	-78	dB
V_o	output voltage	IMD = -60 dB	[6]	64.5	66	-	dBmV
			[7]	65.5	67	-	dBmV
			[8]	67.5	69	-	dBmV
		CTB compression = 1 dB; 129 chs flat; $f = 859.25\text{ MHz}$		48.5	49.5	-	dBmV
		CSO compression = 1 dB; 129 chs flat; $f = 860.5\text{ MHz}$		50	53	-	dBmV
F	noise figure	$f = 50\text{ MHz}$	-	4.5	5	dB	
		$f = 550\text{ MHz}$	-	5	5.5	dB	
		$f = 750\text{ MHz}$	-	5.5	6.5	dB	
		$f = 900\text{ MHz}$	-	6.5	8	dB	
I_{tot}	total current consumption (DC)		[9]	405	420	435	mA

[1] Tilt = 9 dB (50 MHz to 550 MHz); tilt = 3.5 dB at -6 dB offset (550 MHz to 750 MHz).



[2] Tilt = 12.5 dB (50 MHz to 860 MHz).


[3] $f_p = 55.25\text{ MHz}$; $V_p = 44\text{ dBmV}$; $f_q = 805.25\text{ MHz}$; $V_q = 44\text{ dBmV}$; measured at $f_p + f_q = 860.5\text{ MHz}$.

[4] $f_p = 55.25\text{ MHz}$; $V_p = 44\text{ dBmV}$; $f_q = 691.25\text{ MHz}$; $V_q = 44\text{ dBmV}$; measured at $f_p + f_q = 746.5\text{ MHz}$.

[5] $f_p = 55.25\text{ MHz}$; $V_p = 44\text{ dBmV}$; $f_q = 493.25\text{ MHz}$; $V_q = 44\text{ dBmV}$; measured at $f_p + f_q = 548.5\text{ MHz}$.

- [6] Measured according to DIN45004B: $f_p = 851.25$ MHz; $V_p = V_o$; $f_q = 858.25$ MHz; $V_q = V_o - 6$ dB; $f_r = 860.25$ MHz; $V_r = V_o - 6$ dB; measured at $f_p + f_q - f_r = 849.25$ MHz.
- [7] Measured according to DIN45004B: $f_p = 740.25$ MHz; $V_p = V_o$; $f_q = 747.25$ MHz; $V_q = V_o - 6$ dB; $f_r = 749.25$ MHz; $V_r = V_o - 6$ dB; measured at $f_p + f_q - f_r = 738.25$ MHz.
- [8] Measured according to DIN45004B: $f_p = 540.25$ MHz; $V_p = V_o$; $f_q = 547.25$ MHz; $V_q = V_o - 6$ dB; $f_r = 549.25$ MHz; $V_r = V_o - 6$ dB; measured at $f_p + f_q - f_r = 538.25$ MHz.
- [9] The module normally operates at $V_B = 24$ V, but is able to withstand supply transients up to 35 V.






$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 110 chs; tilt = 9 dB (50 MHz to 550 MHz); tilt = 3.5 dB at -6 dB offset (550 MHz to 750 MHz).

- (1) V_o .
- (2) Typ. +3 σ .
- (3) Typ.
- (4) Typ. -3 σ .


Fig 3. Composite second order distortion as a function of frequency under tilted conditions



$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 129 chs; tilt = 12.5 dB (50 MHz to 860 MHz).

- (1) V_o .
- (2) Typ. +3 σ .
- (3) Typ.
- (4) Typ. -3 σ .


Fig 4. Composite triple beat as a function of frequency under tilted conditions



$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 129 chs; tilt = 12.5 dB
(50 MHz to 860 MHz).

- (1) V_o .
- (2) Typ. +3 σ .
- (3) Typ.
- (4) Typ. -3 σ .


Fig 5. Cross modulation as a function of frequency under tilted conditions



$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 129 chs; tilt = 12.5 dB
(50 MHz to 860 MHz).

- (1) V_o .
- (2) Typ. +3 σ .
- (3) Typ.
- (4) Typ. -3 σ .


Fig 6. Composite second order distortion as a function of frequency under tilted conditions



$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 129 chs;
 $f_m = 859.25 \text{ MHz}$.

- (1) Typ. +3 σ .
- (2) Typ.
- (3) Typ. -3 σ .

Fig 7. Composite triple beat as a function of output voltage



$Z_S = Z_L = 75 \Omega$; $V_B = 24 \text{ V}$; 129 chs; $f_m = 860.5 \text{ MHz}$.


- (1) Typ. +3 σ .
- (2) Typ.
- (3) Typ. -3 σ .

Fig 8. Composite second order distortion as a function of output voltage

6. Package outline

Rectangular single-ended package; aluminium flange; 2 vertical mounting holes; 2 x 6-32 UNC and 2 extra horizontal mounting holes; 7 gold-plated in-line leads

SOT115J



DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A ₂ max.	b	c	D max.	d max.	E max.	e	e ₁	F	L min.	p	Q max.	q	q ₁	q ₂	S	U ₁	U ₂	W	w	x	y	Z max.
mm	20.8	9.1	0.51 0.38	0.25	27.2	2.54	13.75	2.54	5.08	12.7	8.8	4.15 3.85	2.4	38.1	25.4	10.2	4.2	44.75 44.25	8.2 7.8	6-32 UNC	0.25	0.7	0.1	3.8

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT115J						-99-02-06 04-02-04

Fig 9. Package outline SOT115J

7. Revision history

Table 6. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BGD902_8	20070607	Product data sheet		BGD902_7
Modifications:				
			<ul style="list-style-type: none"> The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. Legal texts have been adapted to the new company name where appropriate. Table 5 "Characteristics": updated values of s_{11} and s_{22}. 	
BGD902_7	20050308	Product data sheet		BGD902_902MI_6
BGD902_902MI_6	20011102	Product specification		BGD902_902MI_5
BGD902_902MI_5	19990329	Product specification		BGD902_N_3 and BGD902MI_N_1
BGD902_N_3	19980709	Preliminary specification		BGD902_N_2
BGD902_N_2	19980609	Preliminary specification		BGD902_1
BGD902_1	19980312	Preliminary specification		-
BGD902MI_N_1	19980831	Preliminary specification		-

8. Legal information

8.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

8.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

8.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

8.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

9. Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, send an email to: salesaddresses@nxp.com

10. Contents

1 Product profile 1

1.1 General description 1

1.2 Features 1

1.3 Applications 1

1.4 Quick reference data 1

2 Pinning information 1

3 Ordering information 2

4 Limiting values 2

5 Characteristics 2

6 Package outline 7

7 Revision history 8

8 Legal information 9

8.1 Data sheet status 9

8.2 Definitions 9

8.3 Disclaimers 9

8.4 Trademarks 9

9 Contact information 9

10 Contents 10

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.



© NXP B.V. 2007.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 7 June 2007

Document identifier: BGD902_8