

October 2013

Power Supplies Selection Guide

Model	HM7042-5	HM8143	HMP2020	HMP2030	HMP4030	HMP4040
Outputs	2+1	2+1	1+1	3	3	4
Output Power	2 X 0-32V/2A + 0-5.5V/5A	2 X 0-30V/2A + 5V/2A	1 X 0-32V/10A + 1 X 0-32V/5A	3 X 0-32V/5A	3 X 0-32V/10A	4 X 0-32V/10A
Resolution	10mV/1mA	10mV/1mA	1mV/0.1mA	1mV/0.1mA	1mV/0.1mA	1mV/0.1mA
Output Protection	Y	Y	Y	Y	Y	Y
Floating Outputs	Y	Y	Y	Y	Y	Y
Programmable	N	Y	Y	Y	Y	Y
Interfaces	N	USB+ RS232 +GPIB(OPTION)	USB+ RS232 +(GPIB,LAN (OPTION))	USB+ RS232 +(GPIB,LAN (OPTION))	USB+ RS232 +(GPIB,LAN (OPTION))	USB+ RS232 +(GPIB,LAN (OPTION))
Output Ripple	100uVrms	5mVrms	150uVrms	150uVrms	150uVrms	150uVrms
Arbitrary Function	N	Y	Y	Y	Y	Y
Measuring Function	N	Y	Y	Y	Y	Y
Loading Function	N	Y	N	N	N	N

alex.g@easx.co.il
alon.golan@easx.co.il
eli.raz@easx.co.il

לפרטים נוספים : אלכס גנייזר, טל': 03-6458706
נייד: 050-8885625
אלון גולן, טל': 03-6458714
נייד: 050-5285529
אלי רז, טל': 03-6458620
נייד: 050-5452457

